

EL3020 Sash Lockcase

Standards

Standards & Testing	Certified to EN12209
	Fire tested to China Certification Center for Fire Products (CCCF) standards
	Tested to China National Standard GB12955, "Fire resistant doorsets", for 90 minutes
	DIN18251-compliant lockcase dimensions
	Locks tested:
	Latchbolt durability - 200,000 cycles
	Deadbolt durability - 50,000 cycles
	Corrosion resistance - 96h salt spray test


Specifications

Functions	Dead lock, sash lock, bathroom lock, latch, night latch, ball lock
Dimensions	Case dimensions (LxWxD): 165mmx89mmx15mm
	Faceplate dimensions: 235mmx 20mm x3mm; 235mmx 24mm x3mm
	Backset: EL3000: 60mm ; EL3000-b55: 55mm
	Follower to cylinder centres: 72mm
	Dead throw: 12mm
	Latch throw: 20mm
	Door thickness: 40-50mm(standard) or 40-60mm(optional)
Materials & Features	Deadbolt: 304 cast stainless steel
	Latchbolt: 304 cast stainless steel
	Faceplate: 304 stainless steel (square and round optional)
	Strike plate: 304 stainless steel, with preformed lip, nonhanded
Standard Fasteners	Supplied 304 stainless steel machine screws and wood screws as standard

Finishes







EL3020/EL3020-b55 Sash Lockcase

The latch bolt is retracted from both sides by lever handles. Depending on the cylinder selected, the deadbolt can be thrown or retracted from one or both sides. The latch is also controllable by the cylinder.

Unit: mm

Order Specifications - Lockcase

