

EL3020 Sash Lockcase

#### **Standards**

Standards & Testing	Certified to EN12209
	Fire tested to China Certification Center for Fire Products (CCCF) standards
	Tested to China National Standard GB12955, "Fire resistant doorsets", for 90 minutes
	DIN18251-compliant lockcase dimensions
	Locks tested:
	Latchbolt durability - 200,000 cycles
	Deadbolt durability - 50,000 cycles
	Corrosion resistance - 96h salt spray test


## **Specifications**

Functions	Dead lock, sash lock, bathroom lock, latch, night latch, ball lock
Dimensions	Case dimensions (LxWxD): 165mmx89mmx15mm
	Faceplate dimensions: 235mmx20mmx3mm; 235mmx24mmx3mm
	Backset: EL3000: <b>60mm</b> ; EL3000-b55: <b>55mm</b>
	Follower to cylinder centres: 72mm
	Dead throw: 12mm
	Latch throw: 20mm
	Door thickness: 40-50mm(standard) or 40-60mm(optional)
Materials & Features	Deadbolt: 304 cast stainless steel
	Latchbolt: 304 cast stainless steel
	Faceplate: 304 stainless steel (square and round optional)
	Strike plate: 304 stainless steel, with preformed lip, nonhanded
Standard Fasteners	Supplied 304 stainless steel machine screws and wood screws as standard

## **Finishes**







# EL3050/EL3050-b55 Night Latch

Latchbolt is retracted by key outside or by lever inside. Outside lever is always in-operative. Guard latch deadlocks latchbolt when the door is closed. No deadbolt is available.

#### **Order Specifications - Lockcase**

