

SCHLAGE

EC900 Series

EN Certified Cylinder



Schlage EC900 Series

EN Certified Cylinder




Schlage E series cylinder conforms to EN1303-2006 standard. 6 or 5 pins cylinder (6 pins for cylinder edge $\geq 35.5\text{mm}$; 5 pins for cylinder edge $< 35.5\text{mm}$) and 3 nickel-plated brass keys are applied with 6 cylinder types to meet different functional and installation requirements. 4 keyways of Classic and Everest series are available with 8 optional finishes. Up to 4 level master key system which can integrate with ANSI cylinders.

Keyway

Classic keyway: Schlage C (std.), Schlage E
 Everest high-security keyway: Schlage C125, Schlage C145,
 Everest keys are high security keys with undercut groove on the side.



Schlage Classic C



Schlage Classic E



Schlage Everest C125



Schlage Everest C145

Key

Standard Key



Material:
 nickel-plated brass
 Amount: 3 keys (std)

Master Key

MK




Material:
 nickel-plated brass
 Amount: 3 keys (std)

GGMK



Material:
 cupronickel
 Amount:
 Vary by application


Cylinder Type and Dimensions




EC901
 Single cylinder




EC902
 Double cylinder




EC903
 Single cylinder
 w/ thumbturn



EC904
 Bathroom cylinder



EC905
 Off-center
 double cylinder



EC906
 Off-center single cylinder
 w/ thumbturn

	Function	Ref. No	Length (Unit: mm)
Dimension (mm)	Single cylinder	EC901	40/42.5/45/50/55/60/65/70/75/80/85/90
	Double cylinder	EC902	60/65/68/71/76/80/85/90/100/105/110/115
	Single cylinder w/ thumbturn	EC903	60/65/71/76/80/85/90/100/110/120/130/140/200
	Bathroom cylinder	EC904	60/65/71/76/80/85
	Off-center double cylinder	EC905	Vary by application
	Off-center single cylinder w/ thumbturn	EC906	Vary by application